



Medium-duty 1-3/8" Insulated Sectional Door

Amarr® 2731





Solid commercial construction meets variety and style.

The Amarr 2731 is built with two 27-gauge steel skins surrounding 1-3/8" HFC-free polystyrene. The multi-step insulation system includes tongue and groove construction, HFC-free polystyrene insulation and weather stripping that provides a solid wall of protection against the elements.


The exterior steel skin features a flush profile with woodgrain embossment for a more upscale look reminiscent of typical residential doors. The interior skin features a flush profile with stucco embossment for a clean interior surface.



CONSTRUCTION

R-Value 6.7 Amarr 2731
Medium-duty, 1-3/8" 27-gauge steel

TRIPLE-LAYER Steel + Insulation + Steel



Track: All Amarr doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit www.amarr.com.

Springs: Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

Standard Hardware: Galvanized steel hinges and track brackets. All rollers have minimum 10-ball bearings.

SPECIFICATIONS

	Medium-duty Amarr 2731
EXTERIOR STEEL THICKNESS	27 ga
PANEL DESIGN	Flush
STEEL EMBOSSMENT	Woodgrain
DOOR THICKNESS	1-3/8" [3.5cm]
CONSTRUCTION LAYERS	Triple
INSULATION ¹	Polystyrene
R-VALUE ²	6.7
MINIMUM WIDTH	6'
MAXIMUM WIDTH	18' 2"
MINIMUM HEIGHT	7'
MAXIMUM HEIGHT	14' 1"
WIND LOAD ³ AVAILABLE	•
PAINT FINISH WARRANTY ⁴	10 Years
WORKMANSHIP/HARDWARE WARRANTY ⁴	1 Year

¹ Insulation has passed self-ignition, flamespread and smoke developed index fire testing.

² Calculated door section R-value is in accordance with DASMA TDS-163.

³ It is your responsibility to make sure your garage door meets local building codes.

⁴ For complete warranty details, visit amarr.com or contact your local Amarr dealer.



Rapid Install Vertical Lift: Designed specifically for commercial warehouse and dock doors and saves approximately 20 minutes of installation time per door due to fewer jamb attachments and a pre-assembled, one-piece track. Available for door sizes up to 9'4"x10'. For more information, please visit www.amarr.com.

PANEL



FLUSH PANEL WITH WOODGRAIN EMBOSSMENT

COLORS

 Actual paint colors may vary from samples shown.

TRUE WHITE (TW)



ALMOND (AL)



WICKER TAN (WK)



SANDTONE (ST)



Amarr Color Zone¹
Over 700 SnapDry™ paint colors. Approved list can be found at amarr.com/amarr_color_zone. Your local Sherwin-Williams store can provide SnapDry™ paint chips.



Amarr steel doors are pre-painted; owners can use exterior latex paint for custom colors. Visit amarr.com for painting instructions. Painting your door voids the warranty.

WINDOW OPTIONS



21" x 13" SHORT PANEL*



24" x 6" DOUBLE INSULATED ACRYLIC**



41" x 13" LONG PANEL*

*True White shown; also available in Almond, Wicker Tan, and Sandtone. Available with Clear, Obscure, or Insulated glass.

**Available with black frame only.

Entrematic
165 Carriage Court
Winston-Salem, NC 27105
800.503.DOOR
www.amarr.com



YOUR LOCAL AMARR DEALER:

Fray Pedro de Gante 85, Cimatario, Santiago de Querétaro, Querétaro, México CP 76030

(442) 727-0441

contacto@klh.com.mx

klh de México
www.klh.com.mx